
# SoundEar II<sup>®</sup> Noise Activated Warning Sign






# NoiseMeters

#### **Setting the Noise Limit**

You can set the SoundEar II to provide a visual warning, consisting of a flashing read light, to one of 16 different noise limits ranging from 45 to 115 dB(A).

Use the red wheel at the bottom of the device to select the desired noise limit.



## **Mounting and Powering**



The microphone is located at the bottom of the sign, ensure that it is not covered up. Also avoid mounting close to absorbing materials.

With a power outlet nearby, mount the sign on the wall using an 8-9mm screw at a height of 150-200cm. Ensure it is securely mounted. A VESA mount is also available for more secure or corner mounting.

Connect to the power outlet using the 24VDC adapter that is included.

# Displays



**Green** Sign is on and level is acceptable





Yellow Noise level approaching the limit





**Red** Noise limit has been exceeded



# **Typical Noise Limits**

No disturbing noise High concentration level	35-45 dB(A)
Teaching, office or customer service Unhindered conversation and concentration	45-55 dB(A)
Industrial work without noisy machinery Storage, mounting and laboratory work	60-70 dB(A)
Day care facilities Industrial work with noisy machinery	75-85 dB(A)
Concerts, rehearsal rooms Music schools (short term)	90-105 dB(A)

## Specifications

Physical	Cabinet: Shockproof acrylic Measurements: 256 x 205 x 46mm Weight: 1.5kg
Electrical	Power supply: 24VDC, 250mA Warning: The use of power sources other than the original SoundEar may cause damage not covered by warranty.
Temperature	Operating: 0°C to 50°C Storage: -20°C to 60°C
Measurement Parameters	Frequency: 20Hz to 16kHz Range: 45 to 115 dB(A) Frequency Weighting: A Time Weighting: Slow Deviation: ±3dB
X	The product and any enhancements should be taken to

The product and any enhancements should be taken to separate collection at the end of life. Do not dispose of this product as unsorted municipal waste.

## **Contacting NoiseMeters**

#### **United Kingdom**

K.X

NoiseMeters Limited West End Muston YO14 0ES England

Tel: 0845 680 0312 Fax: 0845 680 0316

Email: info@noisemeters.co.uk Web: www.noisemeters.co.uk

#### International

 Tel:
 +44 1306 770 855

 Fax:
 +44 845 680 0316

 Email:
 info@noisemeters.com

 Web:
 www.noisemeters.com

#### **North America**

#### NoiseMeters, Inc.

3233 Coolidge Hwy, Berkley MI 48072 USA

Tel: 888 206 4377 Fax: 888 584 2230

Email: info@noisemeters.com Web: www.noisemeters.com

© NoiseMeters Limited 2020 SoundEar is a registered trademark of SoundEar A/S